



NEXT GEN SMART AI TRANSMITTER



The Swift is the next generation of smart AI transmitters. It listens for other transmitters, transmits when the channel is clear and avoids collision with other signals. Divers can now pair the Swift with an air-integrated Shearwater computer to complete their ultimate dive computer system.

- Powerful yet only 76 x 34mm in size with a greater depth rating of 200msw
- Provides a clear signal transmission reliably
- LED status indicator for signals
- Allows divers to use multiple transmitters
- Backward compatible with all Shearwater air-integrated dive computers
- Designed and built in Canada



AI TRANSMITTER

With the intuitive AI technology built into the Swift, divers can use multiple transmitters reliably with a lower likelihood of dropped communications.

This Next Gen smart AI transmitter is designed and built in Canada for demanding divers of all proficiency levels.

Learn more about the Swift at:
www.shearwater.com/products/swift

SWIFT SPECIFICATIONS

Size	76mm (L) x 34mm (D)
Weight	135g
Depth limit	200msw
Operating temperature range	+4C to +34C
Short-term (hours) temperature range	-10C to +50C
Pressure port	7/16" - 20NF
Rated air pressure	300 bar/4350 psi
Pressure reporting resolution	0.14 bar / 2 psi
HP port proof pressure	450 bar / 6525 psi
Accuracy	5% full scale
Zero offset	< 3.5 bar (50 psi)
Activation pressure	7 bar (100 psi)
De-activation pressure	3.5 bar (50 psi)
Cover screws	1.5mm hex
Body o-ring	24 x 1.5mm
HP port o-ring	AS568-904 75A
Battery type	CR2 3V (User replaceable)
Battery operating life	300 dive hours (HP pressure present) 5 year storage time



www.shearwater.com

